## Refrigerated Condenser Weekly Pressure/Temperature Log Perchloroethylene Dry Cleaners

NESHAP M, §63.323(a) requires weekly measurements be made when a refrigerated condenser is used to comply with §63.322(a)(1) or (b)(1).

- 1. If you have a **transfer machine washer** equipped with a refrigerated condenser, you must measure and record the inlet and outlet temperature. Measurements must be made once a week. The difference (outlet minus inlet) must be 20 °F or greater. If the temperature difference is less than 20 °F, you should make repairs or adjustments and log all changes.
- 2. If you have a **dryer, reclaimer, or a dry-to-dry unit** with a refrigerated condenser, you must measure and record the refrigeration system high pressure and low pressure during the drying phase to determine if they are in the range specified in the manufacturer's operating instructions. If the machine is not equipped with refrigeration system pressure gauges, then you must measure the outlet temperature. It must be equal to or less than 45 °F. Measurements must be made once a week. If the pressure is outside the operating range or the temperature is greater than 45 °F, you should make repairs or adjustments and log all changes.

Any needed repair parts must be ordered within 2 working days of detecting such a parameter value, and must be installed within 5 working days after receipt.

Date	Inspector's Name	Machine Number	Transfer Machine Washer			Dryer, Reclaimer, or Dry-to-Dry Machine		
			Temperature (°F)			Pressure (psig)		Temp.
			Outlet	Inlet	Difference	High	Low	( I')

DEQ FORM # 100-310-H ADOPTED 3/12/08